



BAZR2.MH64379 - Batteries, Standby - Component

Batteries, Standby - Component

KiloVault LLC
 330 Codman Hill Rd.
 Boxborough, MA 01719 United States

MH64379

Model	Capacity, Ah	Voltage, Vdc	Max Discharge		Max Charge		Oper. Range/	Battery Case	Enclosure	High-rate Discharge
			Rate	Rate	Rate	Rate	Max Ambient			
Sealed cell, lead acid batteries with pressure release vents										
2100 PLC	170	12	-	-	-	-	-	V-0	-	-
2V 1000 XLC	1000	2	-	-	-	-	-	V-0	-	-

Marking: Company name and model designation and the Recognized Component Mark, .

Last Updated on 2021-04-01

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."